## 4260

## 12" Parallelogram Jointer





MASSIVE RIBBED cast iron construction ensures flatness, stability & longevity.



**FENCE** 

Rack & pinion fence allows for quick & precise adjustments.



STANDARD helical cutterhead with GERMAN CARBIDE inserts is included with jointer.

Model No.	4260
Stock No. (Helical)	4260.101.4S (3HP, 1Ph)
Stock No. (Helical)	4260.102.4S (5HP, 3Ph)
Infeed Table Travel	3/4"
Cutterhead Speed	6000 RPM
Rabbeting Capacity	3/4"
Dust Port Diameter	6"
Table Dimensions	88"L x 12-1/8"W
Table Height	34"
Fence Dimensions	60-1/4"L x 5-3/8"W
Fence Tilts	135° , 90° & 45°
Positive Stops	90° and 45°
Footprint - Base	21-1/2" x 50-1/2"
Footprint - with Table	88" x 50-1/2"
Motor (1Ph)	3HP, 220V
Motor (3Ph)	5HP, 220V/440V* Prewired 220V (11.6 Amps 220V, 5.8 Amps 440V)
Overall Dimensions	88"L x 40"W x 41"H
Gross Weight	1,020 lbs
	• • • • • • • • • • • • • • • • • • • •



LARGE HAND WHEEL FOR **EASY DEPTH ADJUSTMENTS** 

- Extra-long precision ground tables provide a stable work surface.
- Fully enclosed cabinet for better dust management.
- Helical cutter head includes German-made carbide inserts.
- Carbide inserts are indexed for quick changing.
- Parallelogram design produces smooth accurate cuts.
- Front mounted hand wheels for quick precise adjustments.
- Extra-long precision ground fence tilts 45 degrees both directions with stops.
- Rack and pinion fence adjustment for quick easy set-up.
- High mounted controls include emergency stop.
- Powerful Baldor TEFC motor available in single or threephase.

<sup>\*</sup>Optional 440/460 volt available special order only. Additional cost/parts may apply.